

## P-05

### MULTI-PURPOSE DOUBLE-COATED SPLICING AND MOUNTING TAPE

#### PRODUCT DESCRIPTION

An extremely strong adhesive coated on both sides of a paper carrier has been perfectly engineered for various applications such as splicing and core starting.

#### FEATURES

- Coated on both sides with an aggressive synthetic rubber adhesive that will form a permanent high shear bond to most non-plasticized surfaces.
- Thick, tough impregnated crepe paper adds to the body of fabricated leather goods and other materials and applications as needed.

#### PRODUCT CONSTRUCTION

SYNTHETIC RUBBER
IMPREGNATED CREPE PAPER
SYNTHETIC RUBBER
LINER

#### APPLICATION

- Used for static splices in the paper and processing industries.
- Thick, tough carrier adds to the body of fabricated goods.
- An ideal product for permanent mounting of name plates, signs and trim.
- Can be used for the bonding of leather and garments during fabrication.

#### PROPERTIES, CERTIFICATIONS AND SPECIFICATIONS

<b>Carrier</b>	Impregnated crepe paper	
<b>Adhesive</b>	Synthetic rubber	
<b>Color</b>	Beige	
	<b>Imperial</b>	<b>Metric</b>
<b>Total Tape Thickness</b>	5.5 mil	0.137 mm
<b>Tensile Strength</b>	16 lb./ in	28.4 N/10 mm
<b>Elongation</b>	5%	5%
<b>Adhesion to Steel</b>	95 oz./ in	10.6 N/10 mm
<b>Unwind @ 150 FPM</b>	80 oz/ in	8.9 N/ 10 mm

\*CAUTION: The above are typical values and should not be used in writing specifications. Customer is responsible to ensure product meets intended application requirements before approved for use.

### GENERAL STORAGE CONDITIONS

Best stored between 50°F-80°F / 10°C-27°C, 25-50% relative humidity; out of direct sunlight.

### PRECAUTION REMINDER

Surface should be clean, free of oil, moisture and dirt before applying. Pressure-sensitive adhesive tapes may require pressure by roller, hand or press when applying. Not doing so may affect the general properties and appearance. Please inspect your surface prior to application; this tape may not adhere well to extremely uneven or distorted surfaces. Please remember to allow adequate time for full adhesive strength.

### WARRANTY INFORMATION

Unless Nitto agrees otherwise in a written agreement signed by Nitto, the warranty information and other terms of sale can be found in the Nitto Terms and Conditions of Sale in the legal section of [www.nittousa.com](http://www.nittousa.com) and are hereby incorporated by reference.

### TECHNICAL SUPPORT

For questions pertaining to this data sheet or for additional product information; please email us directly at [support.us@nitto.com](mailto:support.us@nitto.com)